

6

Scotch[®]

BRAND

MAGNETIC TAPE



1/4 INCH x 1200 FEET

(6.35mm x 360m)

SILICONE LUBRICATED

1.5 MIL POLYESTER BACKING

202



7 INCH REEL · SPLICE FREE · PROFESSIONAL

DYNARANGE[®] SERIES



3M
COMPANY

MAKING TIGHT, NOISE-FREE SPLICES



Archivo de Biblioteca UNTREF
 Fondo/Colección *ARIZADA*
 Caja/cajón N°.....
da.....
 Inventario N°: *000463-2*

Do not use magnetized scissors or razor blades when splicing. Magnetized instruments will cause a "click" or "pop" at the splice.

1. Overlap the two ends of the tape and cut them diagonally. (A diagonal cut minimizes disturbance at the splice.)
2. Align both ends with the uncoated side up. Avoid excessive handling of tape.

Brand Splicing Tape No. 41. Apply it diagonally, pressing firmly to make a tight splice. "SCOTCH" Splicing Tape is recommended because it doesn't ooze, always holds tight, passes easily over recorder

Contaminati
body oils or
firm splice.
3. Cover a

BOBINA 6

FOR B



No. 41—Splicing T
 A pressure-se
 tape expressly r
 neat, noiseless
 Makes strong e
 ing splices that
 get stronger w
 Won't get gum
 sticky, won't
 bleed under
 Available in 7/
 long rolls or 1/
 on convenient
 dispenser.

1.- El ombligo de los limbos, la momia y una encuesta

SEGUNDA PARTE

(de la grabación realizada para Edul)

SIN LOS POEMAS CANTADOS

Vel. 15

Banda entera

Stereo